

500006 & 500046

Leda 6ft Twin Standard & Emergency



Our Leda range has been upgraded to 4 Power Selectable outputs, it helps reduce the number of SKUs required – making it a stock friendly solution for wholesalers and contractors alike.

Ideal for commercial and retail environments, each unit also includes a 3-CCT switch (3000K/4000K/6000K), high-quality Tridonic driver, and a hinged body for easier installation. Dimmable and emergency versions are also available.

FEATURES

- 3-CCT – switch between 3000K/4000K/6000K
- 4 Power Selectable - 33W/41W/50W/60W
- High Quality integrated LED Chips
- 5-Year Warranty
- IP20 Rated
- Hinged opening for easy installation
- Compatible with PIR or microwave sensors
- Powered by Tridonic



IP20



3CCT



Warranty



Four Wattage



UK
CA



CE



TRIDONIC
powered by

AVAILABLE OPTIONS



Dali
Dimmable



1-10V
Dimmable



Push
Dimmable



Emergency



Sensor

Code	Description	Wattage	Colour	Lumens
500006	6ft Twin 60W Leda LED Batten Fitting	60W	3000/4000/6000K	7500/8100/7800
500066	6ft Twin 60W Leda LED Batten Fitting - EM	60W	3000/4000/6000K	7500/8100/7800
500006 - DD	6ft Twin 60W Leda LED Batten Fitting - DALI DIM	60W	3000/4000/6000K	7500/8100/7800
500006 - SD	6ft Twin 60W Leda LED Batten Fitting - PUSH/SWITCH DIM	60W	3000/4000/6000K	7500/8100/7800
500006 - AD	6ft Twin 60W Leda LED Batten Fitting - 1-10V DIM	60W	3000/4000/6000K	7500/8100/7800
Set to 39W as Standard				

TECHNICAL SPECIFICATION

LED Type/Qty	SMD2835/80
Lumen Efficacy	150
Colour Temperature	3000/4000/6000K
Colour index	Ra80
Dimming Options Available	DALI/1-10V/PUSH
Input Voltage	220-240V
Driver output Current (max)	0.35A
Driver output Voltage	84-200V
IP Rating	IP20
Operating Temperature	-20 °C ~ +40 °C
Lumen Maintenance	L80B10

0113 426 8300

sales@performance-lighting.co.uk

Unit B8, Astra Business Park,
Parkside Lane, Leeds LS11 5SZ

www.performance-lighting.co.uk



500006 & 500046

Leda 6ft Twin Standard & Emergency



TECHNICAL SPECIFICATION

Switching Cycles	25000
Power Factor	>0.9
Warranty	5 years
Beam Angle	120°
Energy Rating Range	C
Overall Dimensions	1732*62*74mm
Height (mm)	74
Product Weight (Kg)	1.6
IK Rating	IK06
Origin of Manufacturer	China
Driver Manufacturer	Tridonic
EMC Compliant (EN55015)	YES
Primary Material	Steel/PC
Inner Diffusor	PC
Driver Housing	Steel
CE Marked	YES
UKCA Marked	YES
Inrush Current Values	20A/90µs
4 Selectable Power	33/41/50/60w
Luminous Flux (4000K)	4935/6093/7450/8929lm

EMERGENCY TECHNICAL SPECIFICATION

Battery specification	6.4V 1500mAh
Emergency power	3W
Emergency Lumen	300lm
Charging time	24hrs
Class	I
Input Electrical Connections	Quick Connect
Load Voltage (DC) On Em Module	160VDC
Minimum Battery Run Time	3hrs
Recharge Time	3hrs

0113 426 8300

 sales@performance-lighting.co.uk

Unit B8, Astra Business Park,
Parkside Lane, Leeds LS11 5SZ
www.performance-lighting.co.uk

