

# 500201

## Phoenix Pro Surface Linear 4ft



Our Phoenix range has been upgraded to feature 4 selectable power outputs in a single fitting – offering greater flexibility on-site while helping to streamline stock for contractors and wholesalers. Designed for educational and commercial settings such as classrooms, lecture halls, and corridors, Phoenix is a high-performance linear LED solution that combines 3-CCT switching and 125 lm/W efficiency for maximum adaptability and performance. Available in 4ft, 5ft, and 6ft versions, with emergency and dimmable options, Phoenix is built to meet the needs of modern projects with ease and reliability.

### FEATURES

- 3-CCT – switch between 3000K/4000K/6000K
- High Quality integrated LED Chips and driver
- 5-Year Warranty
- Durable polycarbonate housing and cover
- IP20 Rated
- Compatible with PIR and microwave sensors
- Dimmable and emergency versions available
- Stainless steel clips as standard
- Tridonic Driver



IP20



3CCT



Warranty



Four Wattage



powered by  
**TRIDONIC**

### AVAILABLE OPTIONS



Dali  
Dimmable



1-10V  
Dimmable



Push  
Dimmable



Emergency



Sensor

Code	Description	Wattage	Colour	Lumens
500201	Phoenix Pro 4ft Dual Wattage	20W & 38W	3000/4000/6000K	4650/4750/4700
500201-DD	Phoenix Pro 4ft Dual Wattage - DALI DIM	20W & 38W	3000/4000/6000K	4650/4750/4700
500201-SD	Phoenix Pro 4ft Dual Wattage - PUSH/SWITCH DIM	20W & 38W	3000/4000/6000K	4650/4750/4700
500201-AD	Phoenix Pro 4ft Dual Wattage - 1-10V DIM	20W & 38W	3000/4000/6000K	4650/4750/4700

### TECHNICAL SPECIFICATION

LED Type/Qty	SMD2835/126
Lumen Efficacy	125lm/w
Colour Temperature	3000/4000/6000K
Colour index	Ra80
Dimming Options Available	DALI/1-10V/PUSH
Input Voltage	220-240v
Driver output Current (max)	0.35A

0113 426 8300

sales@performance-lighting.co.uk

Unit B8, Astra Business Park,  
Parkside Lane, Leeds LS11 5SZ

www.performance-lighting.co.uk



# 500201

## Phoenix Pro Surface Linear 4ft

### TECHNICAL SPECIFICATION

Driver output Voltage	50-133V
IP Rating	IP20
Operating Temperature	-20°C ~ +40°C
Lumen Maintenance	L80B10
Switching Cycles	25000
Power Factor	>0.9
Warranty	5 years
Beam Angle	120°
Energy Rating Range	D
Overall Dimensions	1190*200*81mm
Height (mm)	81mm
Product Weight (Kg)	2.2
IK Rating	IK06
Origin of Manufacturer	China
Driver Manufacturer	Tridonic
EMC Compliant (EN55015)	YES
Primary Material	PC/Steel
Inner Diffusor	PC
Driver Housing	Steel
CE Marked	YES
UKCA Marked	YES
Inrush Current Values	24A/220µs
4 Selectable Power	22/27/33/39w
Luminous Flux (3000K)	2477/3045/3678/4438lm
Luminous Flux (4000K)	2764/3345/4093/4925lm
Luminous Flux (6000K)	2657/3182/3956/4648lm

