100021 **ANILLO 15W 3CCT LED Round Panel**









The Anillo series is a versatile range of slimline, high-efficiency 3-CCT LED recessed panels, designed for reliable performance across a variety of commercial settings — including offices, retail, and hospitality environments.

Built with quality components, these panels offer excellent energy savings and smooth, uniform light distribution. A Tp(b) rated diffuser is included to meet standard ceiling requirements without compromise.

FEATURES

- Panel Mounted 3CCT
- Switch from 3000k/4000k/6000k
- · Quality LED chip
- Tp(b) rated diffuser
- IP44 Rated
- · Slimline design finished in white
- 3 year warranty
- Dimmable and Emergency versions available









3CCT

AVAILABE OPTIONS









Dali 1-10V Push Dimmable Dimmable

Emergency

| Code | Description | Wattage | Colour | Lumens |
|-------------|---|---------|---------------------|--------|
| 100021 | ANILLO 15W 3CCT LED Round Panel | 15W | 3000 / 4000 / 6000K | 1400lm |
| 100021 - EM | ANILLO 15W 3CCT LED Round Panel - EMERGENCY | 15W | 3000 / 4000 / 6000K | 1400lm |
| 100021 - DD | ANILLO 15W 3CCT LED Round Panel - DALI DIM | 15W | 3000 / 4000 / 6000K | 1400lm |
| 100021 - SD | ANILLO 15W 3CCT LED Round Panel - PUSH/SWITCH DIM | 15W | 3000 / 4000 / 6000K | 1400lm |
| 100021 - AD | ANILLO 15W 3CCT LED Round Panel - 1-10V DIM | 15W | 3000 / 4000 / 6000K | 1400lm |

TECHNICAL SPECIFICATION

| LED Type/Qty | SMD2835/90 |
|-----------------------------|-----------------|
| Lumen Efficacy | 95lm/w |
| Colour Temperature | 3000/4000/6000K |
| Luminous Flux | 1400 |
| Colour Index | Ra80 |
| Dimming Options Available | YES |
| Input Voltage | 220-240V |
| Driver Output Current (max) | 0.15A |
| Driver Output Voltage | 30-56V |





Unit B8, Astra Business Park,


100021 ANILLO 15W 3CCT LED Round Panel



TECHNICAL SPECIFICATION

| IP Rating | IP44 |
|-------------------------|-----------------|
| Operating Temperature | 3000/4000/6000K |
| Lumen Maintenance | L80B10 |
| Switching Cycles | 15000 |
| Power Factor | >0.5 |
| Warranty | 3 years |
| Beam Angle | 120 |
| Energy Rating Range | F |
| Overall Dimensions | 190*190*22 |
| Height (mm) | 22mm |
| Product Weight (Kg) | 0.38 |
| IK Rating | IK06 |
| Origin of Manufacturer | China |
| EMC Compliant (EN55015) | YES |
| Primary Material | PC/Steel |
| Diffusor | Tp(b) |
| Driver Housing | PC |
| CE Marked | YES |
| UKCA Marked | YES |









Unit B8, Astra Business Park, Parkside Lane, Leeds LS11 5SZ