## 100019 **ANILLO 9W 3CCT LED Round Panel**









The Anillo series is a versatile range of slimline, high-efficiency 3-CCT LED recessed panels, designed for reliable performance across a variety of commercial settings — including offices, retail, and hospitality environments.

Built with quality components, these panels offer excellent energy savings and smooth, uniform light distribution. A Tp(b) rated diffuser is included to meet standard ceiling requirements without compromise.

#### **FEATURES**

- Panel Mounted 3CCT
- Switch from 3000k/4000k/6000k
- · Quality LED chip
- Tp(b) rated diffuser
- IP44 Rated
- · Slimline design finished in white
- 3 year warranty
- Dimmable and Emergency versions available









3CCT

**AVAILABE OPTIONS** 









Dali 1-10V Push Dimmable Dimmable

Emergency

Code	Description	Wattage	Colour	Lumens
100019	ANILLO 9W 3CCT LED Round Panel	9W	3000 / 4000 / 6000K	855lm
100019 - EM	ANILLO 9W 3CCT LED Round Panel - EMERGENCY	9W	3000 / 4000 / 6000K	855lm
100019 - DD	ANILLO 9W 3CCT LED Round Panel - DALI DIM	9W	3000 / 4000 / 6000K	855lm
100019 - SD	ANILLO 9W 3CCT LED Round Panel - PUSH/SWITCH DIM	9W	3000 / 4000 / 6000K	855lm
100019 - AD	ANILLO 9W 3CCT LED Round Panel - 1-10V DIM	9W	3000 / 4000 / 6000K	855lm

#### **TECHNICAL SPECIFICATION**

LED Type/Qty	SMD2835/54
Lumen Efficacy	95lm/w
Colour Temperature	3000/4000/6000K
Luminous Flux	855
Colour Index	Ra80
Dimming Options Available	YES
Input Voltage	220-240V
Driver Output Current (max)	0.1A
Driver Output Voltage	8-30V



# 100019 **ANILLO 9W 3CCT LED Round Panel**



### **TECHNICAL SPECIFICATION**

IP Rating	IP44
Operating Temperature	3000/4000/6000K
Lumen Maintenance	L80B10
Switching Cycles	15000
Power Factor	>0.5
Warranty	3 years
Beam Angle	120
Energy Rating Range	F
Overall Dimensions	145*145*22mm
Height (mm)	22mm
Product Weight (Kg)	0.24
IK Rating	IK06
Origin of Manufacturer	China
EMC Compliant (EN55015)	YES
Primary Material	PC/Steel
Diffusor	Tp(b)
Driver Housing	PC
CE Marked	YES
UKCA Marked	YES





