

400001 Standard ORION LED Bulkhead Dual Wattage CCT



FEATURES

- 3-CCT: Switch between 3000K/4000K/6500K
- Dual Wattage – Switch between 12w and 16w
- 5 Year warranty
- IP65 rated
- Slimline Design
- Easy to install
- Emergency and microwave sensor options available



IP65



3CCT



Dual
Wattage



Orion is our wattage & colour switchable 3-CCT 12 & 16W LED bulkhead fitting. With long life and high lumen output, this bulkhead is ideal for internal and external use, in most domestic and commercial applications.

AVAILABLE OPTIONS



Emergency



Sensor

Code	Description	Wattage	Colour	Lumens
400001	Orion Bulkhead - Dual Wattage 12/16w – Standard	12/16W	3000K/4000K/6500K	1200/1600lm
100016	Orion Bulkhead POLO Bezel Black	N/A	N/A	N/A
100017	Orion Bulkhead POLO Bezel Chrome	N/A	N/A	N/A

TECHNICAL SPECIFICATION

LED Type/Qty	SMD2835/182
Lumen Efficacy	100lm/w
Colour Temperature	3000K/4000K/6500K CCT
Luminous Flux	1200lm/1600lm
Colour index	Ra>80
Dimming Options Available	DALI / MAINS
Input Voltage	220-240Vac, 50/60Hz
Driver output Current (max)	660mA
Driver output Voltage	DC17-24V
IP Rating	IP65
Operating Temperature	-10°- +40°C
Lumen Maintenance	L70/B50 @ 50,000hrs
Switching Cycles	>25,000
Power Factor	>0.9
Warranty	5 Years
Beam Angle	105°
Thermal Cutout	No

0113 426 8300

sales@performance-lighting.co.uk

Unit B8, Astra Business Park,
Parkside Lane, Leeds LS11 5SZ

www.performance-lighting.co.uk



TECHNICAL SPECIFICATION

Primary Running Current	0.2A
Overall Dimensions	320mm
Height (mm)	82.5mm
Product Weight (Kg)	0.85kg
Class	Class II
IK Rating	IK08
Origin of Manufacturer	China
Driver Manufacturer	Performance Lighting
EMC Compliant (EN55015)	Yes
Construction	Twist & Lock
Driver Housing	Plastic
Standard & Approvals	CE, UKCA
Manufactured in Accordance To	BS EN 60598-2-1
CE Marked	Yes
UKCA Marked	Yes
Input Electrical Connections	N / E / L
Method of fix	Back screw fix or BESA plate mounting
Replaceable (LED only) light source by a professional	Yes
Replaceable control gear by a professional	Yes

